


## iDS-2PT9122IX-DE/S (5-50 mm) (4 mm) PanoVu PT Series 2MP + 2MP Target Capture Camera



Hikvision iDS-2PT9122IX-DE/S (5-50 mm) (4 mm) PanoVu PT Series 2MP + 2MP Target Capture Camera is able to capture distant view images as well as close-up images with the integration design of distant view camera and tracking PTZ camera.

This series of camera can be widely used in the scenes where wide monitoring range and high definition are required, such as the entrance/exit, airport, port, wharf, reservoir, square, park, scenic spot, and station, etc.

### Distant View Camera

- 1/2.7" progressive scan CMOS
- Up to 1920 × 1080 resolution
- Horizontal field of view: 92°
- Min. illumination:  
Color: 0.002 Lux@(F1.0, AGC ON),  
B/W: 0.0005 Lux@(F1.0, AGC ON)

### Tracking PTZ Camera

- 1/2.7" progressive scan CMOS
- Up to 1920 × 1080 resolution
- Horizontal field of view: 61.3° to 6.26°
- Pan and tilt range: 210° (Pan), -22° to 22° (Tilt)
- Min. illumination:  
Color: 0.0035 Lux@(F1.6, AGC ON)  
0 Lux with IR
- 10× optical zoom, 16× digital zoom



## Specification


System	
One-touch Link	Support
Multiple Targets Tracking	Support
Calibration Mode	Auto/Manual
Target Switch Time	<1 s
Calibration	Manual/Auto
Smart Detection	Detects human body, face, and vehicle automatically.
Tracking Time Settings	Support
Distant View Camera	
Image Sensor	1/2.7" Progressive Scan CMOS
Min. Illumination	Color: 0.002 Lux@(F1.0, AGC ON), B/W: 0.0005 Lux@(F1.0, AGC ON)
Focal Length	4.0 mm
Aperture	F1.0
Horizontal FOV	92°
S/N Ratio	>52 dB
3D DNR	Support
Smart Image Enhancement	Digital WDR, Defog, HLC, EIS, BLC
Basic Event Detection	Motion Detection, Video Tampering Detection, Alarm Input, Alarm Output, HDD Full, HDD Error, Network Disconnected, IP Address Conflicted, Illegal Login
Video Compression	H.265+/H.265/H.264+/H.264/MJPEG
Main Stream Resolution	50Hz: 25fps (1920 × 1080, 1280 × 960, 1280 × 720) 50fps (1920 × 1080, 1280 × 960, 1280 × 720) 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720) 60fps (1920 × 1080, 1280 × 960, 1280 × 720)
Sub-Stream Resolution	50Hz: 25fps (704 × 576, 640 × 480, 352 × 288) 60Hz: 30fps (704 × 480, 640 × 480, 352 × 240)
Third Stream Resolution	50Hz: 25fps (1920 × 1080, 1280 × 960, 1280 × 720, 704 × 576, 640 × 480, 352 × 288) 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720, 704 × 480, 640 × 480, 352 × 240)
Tracking PTZ Camera	
Image Sensor	1/2.7" Progressive Scan CMOS
Min. Illumination	Color: 0.0035 Lux@(F1.6, AGC ON), 0 Lux with IR
S/N Ratio	>55 dB
3D DNR	Support
IR	IR distance: 100 m; IR brightness and angle are adjustable.
Smart Image Enhancement	Digital WDR, Defog, HLC, EIS, Smart IR, BLC
Focal Length	5 mm to 50 mm, 10× optical zoom
Zoom Speed	Approx.2.5 s (Optical Wide-Tele)
Horizontal FOV	61.3° to 6.26° (Wide-Tele)
Min. Working Distance	10 mm to 1500 mm (Wide-Tele)
Aperture Range	F1.6 to F3.0
Pan and Tilt Range	Pan: 210°, Tilt: -22° to 22°
Pan and Tilt Speed	Pan Manual Speed: 0.1°/s to 200°/s (Configurable), Pan Preset Speed: 300°/s Tilt Manual Speed: 0.1°/s to 120°/s (Configurable), Tilt Preset Speed: 120°/s
Preset Number	300
Patrol	8 patrols, up to 32 presets per patrol
Park Action	Preset/Patrol Scan
Scheduled Task	Preset/Patrol Scan/Dome Reboot/Dome Adjust/Aux Output
Power-off Memory	Support
Video Compression	H.265+/H.265/H.264+/H.264/MJPEG

Main Stream Resolution	50Hz: 25fps (1920 × 1080, 1280 × 960, 1280 × 720) 50fps (1920 × 1080, 1280 × 960, 1280 × 720) 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720) 60fps (1920 × 1080, 1280 × 960, 1280 × 720)
Sub-Stream Resolution	50Hz: 25fps (704 × 576, 640 × 480, 352 × 288) 60Hz: 30fps (704 × 480, 640 × 480, 352 × 240)
Third Stream Resolution	50Hz: 25fps (1920 × 1080, 1280 × 960, 1280 × 720, 704 × 576, 640 × 480, 352 × 288) 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720, 704 × 480, 640 × 480, 352 × 240)
Audio Compression	G.711alaw/G.711ulaw/G.722.1/G.726/MP2L2/PCM
<b>Network</b>	
Protocols	TCP/IP, IPv4/IPv6, HTTP, HTTPS, 802.1x, Qos, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTCP, RTP, TCP, UDP, IGMP, ICMP, DHCP, PPPoE, Bonjour
API	Open-ended, support ONVIF, ISAPI, and CGI, support HIKVISION SDK and Third-Party Management Platform
Network Storage	Built-in memory card slot, support Micro SD/SDHC/SDXC (up to 256 GB)
Web Browser	IE 8 to 11, Firefox 32.0.1, 38.0, 43.0.1, Chrome 40.0.2214.94
<b>Interface</b>	
Network Interface	1 RJ45 10 M/100 M Ethernet Interface, Hi-PoE
Alarm Input/ Output	1-ch alarm input and 1-ch alarm output, support alarm linkage: Memory Card Recording/Aux Output/Notify Surveillance Center/Upload to FTP/Send Email
Audio Input/ Output	1-ch audio input and 1-ch audio output
<b>General</b>	
Power Supply	12 VDC & Hi-PoE
Power Consumption	45 W Max. (IR 6 W Max.)
Working Temperature	Outdoor: -40°C to 70°C (-40°F to 158°F)
Working Humidity	≤ 90%
Protection Level	IP66 Standard, TVS 6000 V Lightning Protection, Surge Protection and Voltage Transient Protection
Dimension	195.1 mm × 280.8 mm × 174.8 mm (7.68" × 11.06" × 6.88" )
Weight	Approx. 2.5 kg (5.51 lb)

## Available Model

iDS-2PT9122IX-DE/S (5-50 mm) (4 mm), 12 VDC & Hi-PoE

## Dimension



## Accessories



DS-2601ZJ-P  
Wall Mounting Bracket

**Note:**

DS-2601ZJ-P is included. And you should purchase DS-2115ZJ-P in addition. The diameter of the hold hoop is 67 mm to 127 mm.



DS-2665ZJ-P  
Base Mounting Bracket

**Note:**

DS-2665ZJ-P is not included. And you should purchase DS-2115ZJ-P in addition. The diameter of the hold hoop is 67 mm to 127 mm.



### Headquarters

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Europe**  
T +31-23-55-42-770  
info.eu@hikvision.com

**Hikvision Middle East**  
T +971-4-8816086  
salesme@hikvision.com

**Hikvision Russia**  
T +7-495-669-67-99  
saleru@hikvision.com

**Hikvision India**  
T +91-22-28469900  
sales@pramahikvision.com

**Hikvision Italy**  
T +39-0438-6902  
info.it@hikvision.com

**Hikvision France**  
T +33(0)1-85-330-450  
info.fr@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-50  
poland@hikvision.com

**Hikvision UK**  
T +01628-902140  
support.uk@hikvision.com

**Hikvision Singapore**  
T +65-6684-4718  
sg@hikvision.com

**Hikvision Oceania**  
T +61-2-8599-4233  
salesau@hikvision.com

**Hikvision Canada**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Korea**  
T +82-31-731-8841  
sales.korea@hikvision.com

**Hikvision Brazil**  
T +55 11 3318-0050  
Latam.support@hikvision.com

**Hikvision South Africa**  
Tel: +27 (10) 0351172  
sale.africa@hikvision.com

**Hikvision Hong Kong**  
T +852-2151-1761